





누름판방식

참고  
바퀴멈춤방식

R = 0.3이하

로드표면은 0.8~1.6μmRz(0.2~0.4μmRa) 버프(무두질SPBF)처리 하십시오.

• 굵기는 JIS B 0601 : 2001에 의함.  
P는 규정의 평가길이 확보되지 않을 때 적용하십시오.

더스트 셀 호칭 치수 및 장착부 치수							KNS 부품 번호		
d	D	t	h	H	φS	B			
14	24	5	7	5 <sup>+0.5</sup> / <sub>+0.3</sub>	19	4	KAR0513F5		
16	26				21		KAR0677E5		
18	30				25		KAR0815F5		
20	32				27		KAR0995E1		
22	34				29		KAR1121F5		
22.4	34.4	6	9	6 <sup>+0.5</sup> / <sub>+0.3</sub>	29		KAR1203F5		
25	37				32		KAR1301H5		
28	40				35		KAR1536F5		
30	42				37		KAR1664F5		
31.5	44				38.5		KAR1803G5		
32	44				39		KAR1870F5		
35	47				42		KAR2041E5		
35.5	47.5				7		10	7 <sup>+0.5</sup> / <sub>+0.3</sub>	42.5
36	48	43	KBR1418E5						
40	52	47	KAR2342E5						
45	57	52	KAR2633G5						
50	62	57	KAR2831F5						
55	69	62	KAR3033F5						
56	70	63	KAR3089G5						
60	74	67	KAR3187G5						
63	77	8	11	8 <sup>+0.6</sup> / <sub>+0.4</sub>	70		KAR3313F5		
65	79				72		KAR3381F5		
70	84				77		KAR3493F5		
75	89				82		KAR3596G5		
80	94				87		K AR3720I5		
85	99				92	KAR3828F5			
90	104				97	KAR3913E0			
95	109				102	KAR3976G5			
100	114	9	12	9 <sup>+0.6</sup> / <sub>+0.4</sub>	107	KAR4046G5			
105	121				113	KAR4142F5			
110	126				118	KAR4196F5			
112	128				120	KAR4232F5			
120	136				128	KAR4326E5			
125	141				133	KAR4393F5			
140	160				10	14	10 <sup>+0.6</sup> / <sub>+0.4</sub>	150	KAR4533G5
145	165							155	KAR4578E5
150	170	160	KAR4615E5						
155	175	165	KAR4663E5						
160	180	170	KAR4704G5						
170	190	180	KAR4785E5						
175	195	185	KAR4839F5						
180	205	191	KAR4890G5						
200	225	12	17	12 <sup>+0.7</sup> / <sub>+0.5</sub>	212	KAR5048G5			
225	250				237	KAR5245F5			
250	275				262	KAR5396F5			