





R = 0.3이하

로드표면은 0.8~1.6 $\mu$ mRz(0.2~0.4 $\mu$ mRa) 버프(무두질SPBF)처리 하십시오.

- 굵기는 JIS B 0601 : 2001에 의함.  
P는 규정의 평가길이 확보되지 않을 때 적용하십시오.

더스트 셀 호칭 치수 및 장착부 치수					KNS 부품 번호			
d	D	t	h	H				
10	20	5	7	5 <sup>+0.5</sup> <sub>+0.3</sub>	K AR0258E5			
15	25				K AR0586E5			
20	32				K AR0995F5			
22.4	34.4	6	9	6 <sup>+0.5</sup> <sub>+0.3</sub>	K AR1203G5			
25	37				K AR1301F5			
28	40				K AR1536G5			
30	42				K AR1664G5			
35	47				K AR2041F5			
35.5	47.5				K AR2149J5			
40	52				K AR2342F5			
45	57	7	10	7 <sup>+0.5</sup> <sub>+0.3</sub>	K AR2633I5			
50	62				K AR2831H5			
55	69				K AR3033G5			
60	74				K AR3187J5			
65	79				K AR3381G5			
80	94				K AR3720H5			
85	99				K AR3828G5			
90	104				K AR3913F5			
95	109				K AR3976H5			
100	114				K AR4046E5			
105	121	8	11	8 <sup>+0.6</sup> <sub>+0.4</sub>	K AR4142E5			
120	136				K AR4326H5			
130	146				K AR4438E5			
155	175				10	14	10 <sup>+0.6</sup> <sub>+0.4</sub>	K AR4663F5
210	235				12	17	12 <sup>+0.7</sup> <sub>+0.5</sub>	K AR5129E5
230	255	K AR5277E5						
240	265	K AR5336E5						
265	290	K AR5480E5						
300	330	16	22	16 <sup>+0.7</sup> <sub>+0.5</sub>	K AR5622B5			
310	340				K AR5668B5			
315	345				K AR5685B5			
330	360				K AR5741B5			
335	365				K AR5761B5			
440	480				18	22	18 <sup>+0.7</sup> <sub>+0.5</sub>	K AR6021B5
460	490				20	25	20 <sup>+0.8</sup> <sub>+0.6</sub>	K AR6073B5
470	510	K AR6094B5						
500	530	16	22	16 <sup>+0.7</sup> <sub>+0.5</sub>				K AR6140B5